

DC EV Charger
40KW/60KW



Features

- Delicate appearance, simple operation, convenient installation
- High efficiency, reliable and stable performance
- Friendly interaction interface, 7-inch color screen
- Support dual GBT/CCS2/CCS1 connectors
- Support RFID card/ocpp1.6J
- Support Plug&Play
- Overload integrated Protection
- Dual charging connctors

SPECIFICATION

Specification	Model	AE-D 40/60KW
AC NominalInput	Phases/Lines	3-Phase+Neutral+PE
	Voltage	400V±10%
	Frequency	50/60Hz
AC NominalOutput	Voltage	200-1000V
	Current	0-125A/0-200A
	Power	40/60KW
	Power factor	≥0.99 (50%-100% load)
	Efficiency	≥95%
Configurations	Charging Outlet	1*CCS2/2*CCS2
	Cable Length	5M
	LED Indicator	Yes
	LCD Screen	7" touchable screen for charging data
	Emergency Stop	Yes
	RFID Reader	Yes
	RFID Card	2pcs Mifare card
	Energy Meter	MID certified meter for optional
	RCD	Type A
	Network Module	WiFi/LAN/4G for options
	Communication Protocol	OCPP 1.6 Json
Environmental Index	Installation Method	Wall-mounted
	Operation Temperature	-30~+50°C
	Working Humidity	5-95% without condensation
	Working Altitude	2000M
	Protection Grade	IP54
	Application Site	Indoor/Outdoor
	Cooling Method	Forced air cooling
Security Protection	Multiple Protection	Over/Under voltage protection, Overload protection, Short circuit protection,Current leakageprotection, Grounding protection, Surge protection, Over/Under temperature protection
	Safety Standard	IEC 61851-1, IEC 61851-23
	Warranty	2 years
Package Information	Product Dimension	770*560*210mm/900*650*260mm
	Package Dimension	1010*720*510mm/1150*800*510mm
	Net Weight	81KG/93KG
	Gross Weight	86KG/107KG